

Residual Current Circuit Breakers, F 200 Series

Applications: Buildings, both residential and commercial;

Standard: IEC/EN 61008;

Function: Protection against the effects of sinusoidal alternating earth fault currents, protection against indirect contacts and additional protection against direct contacts (with $I_{\Delta n}=30\text{mA}$), command and isolation of resistive and inductive circuits;

Marking: According to IEC 61008;



F202 F-25/0.03



F204 F40/0.03

| Number of Poles | Fault Current | Rated Current, In | Type Code | Order Code | bbn | | |
|-----------------|---------------|-------------------|------------------------|-----------------|---------------|-------|-------------------|
| | | | | | 80 | 12542 | Weight Units/Pack |
| 2 | 30mA | 25 | F 202 F-25/0.03 | 2CSF202325R1250 | 992728 | 0.200 | 1/60 |
| | | 40 | F 202 F-40/0.03 | 2CSF202325R1400 | 992837 | 0.200 | 1/60 |
| | | 63 | F 202 F-63/0.03 | 2CSF202325R1630 | 992936 | 0.200 | 1/60 |
| 4 | 30mA | 25 | F 204 F-25/0.03 | 2CSF204325R1250 | 993032 | 0.350 | 1/30 |
| | | 40 | F 204 F-40/0.03 | 2CSF204325R1400 | 993131 | 0.350 | 1/30 |
| | | 63 | F 204 F-63/0.03 | 2CSF204325R1630 | 993230 | 0.350 | 1/30 |